

## 40X40X10 mm

## KF0410-03 KF0410-08 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** :  $\pm 10\%$

### SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH <sub>2</sub> O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Power (Watt)	Noise (dBA)	Weight (g)					
KF0410B5H-AO	B	5	4.25~5.75	8.09	0.187	7500	0.16	0.80	0.8	31.4	16					
KF0410B5H				6.42	0.129	6000	0.13	0.65	0.8	26.4						
KF0410B5M				5.75	0.106	5400	0.09	0.45	0.5	24.4						
KF0410B5L				4.37	0.067	4200	0.07	0.35	0.4	19.9						
KF0410S5H	S			5	4.25~5.75	6.42	0.129	6000	0.20	1.00		1.2	26.4			
KF0410S5M						5.75	0.106	5400	0.10	0.50		0.8	24.4			
KF0410S5L						4.37	0.067	4200	0.08	0.40		0.6	19.9			
KF0410B1H-AO						B	12	10.2~13.8	8.09	0.187		7500	0.06	0.72	0.8	31.4
KF0410B1H	6.42	0.129	6000						0.06	0.80		0.8	26.4			
KF0410B1M-	5.75	0.106	5400						0.058	0.70		0.7	24.4			
KF0410B1L	4.37	0.067	4200						0.05	0.60		0.6	19.9			
KF0410S1H	S	12	10.2~13.8			6.42			0.129	6000		0.08	0.96	1.2	26.4	
KF0410S1M				5.75	0.106	5400			0.066	0.80		0.8	24.4			
KF0410S1L				4.37	0.067	4200			0.058	0.70		0.7	19.9			
KF0410B2S-AI				B	24	20.4~27.6			8.09	0.187		7500	0.058	1.40	1.4	31.4
KF0410B2S	6.97								0.159	6600		0.05	1.20	1.4	29.3	
KF0410B2H	6.42								0.129	6000		0.05	1.20	1.2	26.4	
KF0410B2M	5.75								0.106	5400		0.04	0.96	1.0	24.4	
KF0410B2L	4.37								0.067	4200		0.03	0.72	0.8	19.9	
KF0410S2H	S						24	20.4~27.6	6.42	0.129		6000	0.05	1.20	1.2	26.4
KF0410S2M									5.75	0.106		5400	0.04	0.96	1.0	24.4
KF0410S2L									4.37	0.067		4200	0.03	0.72	0.8	19.9

Specifications subject to change without notice

The 7<sup>TH</sup> character of Model No means the bearing code. Please refer to the page "PART NUMBER SYSTEM".

Please contact us for detail if your request bearing system is not shown in the above list.

