

## The Zero Screw Solution



### 特点

- 1 插入即可、无螺丝、操作简单
- 2 高接触可靠性独特构造, 保持稳定连接状态
- 3 完全锁扣, 连接时始终保持锁定状态



One Action

Positive-Lock

High-Current

符合JIS C8201-7-1标准

Patented

### 特性

额定电流	产品	D30	D60	D150	D200	D250	D400
	适合线缆		1.25mm <sup>2</sup> =16A 2mm <sup>2</sup> =21A 3.5mm <sup>2</sup> =30A 5.5mm <sup>2</sup> =40A	5.5mm <sup>2</sup> =40A 8mm <sup>2</sup> =50A 14mm <sup>2</sup> =70A	22mm <sup>2</sup> =94A 38mm <sup>2</sup> =132A 60mm <sup>2</sup> =175A	60mm <sup>2</sup> =175A 100mm <sup>2</sup> =240A	150mm <sup>2</sup> =310A
适合线缆		UL, TÜV认证			UL、TÜV计划获得	UL, TÜV认证	
额定电压		600V AC/DC			1000V AC、1500V DC		
耐电压		2500V AC1分钟			5000V AC1分钟		
接触电阻		1mΩ 以下 (1A DC)		0.1mΩ 以下 (1A DC)			
使用温度范围		-25 to +105℃ (包含通电时的温度上升)					
保存温度范围		-10 to +60℃					
绝缘电阻		1000MΩ 以上 (500V DC)					
插拔次数		50次					